



Centrotherm

# Centrocerin®

## Lubricant for plastic pipes

Pipe lubricant Centrocerin® is a white, water miscible paste, used for the assembly of plastic pipes, especially for plumbing and building works.

Due to excellent lubricating and gliding properties pipe lubricant Centrocerin® support the assembly of the pipes and avoid, if used correctly, the deforming of the gasket within the sealing area and thereby protects against leaks. We recommend applying Centrocerin® in sufficient quantities just shortly before the installation of the pipes in order to prevent the drying-up of the lubrication film.

### Properties

- × Centrocerin® has been developed exclusively with synthetic based raw materials.
- × Fulfils the current requirements of the German DVGW institute after the basis of type examination VP 641 in regard to the application for drinking-water systems. (Reg. No.: DW-5163BU0491)
- × Corresponds to the drinking water approval WRAS BS6920-1:2000.



### Features

Composition	Paste
Colour	White
PH-Value	8,5-9,5
Process temperature	between -5° C and +40° C
Packaging	50/250ml tubes
Stock temperature	between +5° C and +25° C and in closed packaging

### Recommendation

We recommend applying Centrocerin® in sufficient quantities just shortly before the installation of the pipes in order to prevent the drying-up of the lubrication film.

This information corresponds with the actual technical standings. Subject to change without notice. All data can not be taken as warranted characteristics for each individual case. They do not absolve the consumer from own verifications. Additional data on request. Rev.2, 12/13